

4.9. DDL1 dictionary

BY S. R. HALL

This is version 1.4.1 of the dictionary definition language (DDL1) that provides a machine-readable description of the attributes of data items in the core CIF and related dictionaries (Chapters 4.1 to 4.4). This version of DDL is described in Chapter 2.5.

category (char)
Character string which identifies the natural grouping of data items to which the specified data item belongs. If the data item belongs in a looped list, then it must be grouped only with items from the same category, but there may be more than one looped list of the same category provided that each loop has its own independent reference item (see list_reference).

[category]

definition (char)
The text description of the defined item.

[definition]

dictionary_history (char)
A chronological record of the changes to the dictionary file containing the definition. Normally this item is stored in the separate data block labelled data_on_this_dictionary.

[dictionary]

dictionary_name (char)
The name string which identifies the generic identity of the dictionary. The standard construction for these names is *<application code>_<dictionary version>.dic*. Normally this item is stored in the separate data block labelled data_on_this_dictionary.

Examples: 'ddl_core.dic', 'cif_core.dic'. [dictionary]

dictionary_update (char)
The date that the dictionary was last updated. Normally this item is stored in the separate data block labelled data_on_this_dictionary.

[dictionary]

dictionary_version (numb)
The dictionary version number. Version numbers cannot decrease with updates. Normally this item is stored in the separate data block labelled data_on_this_dictionary.

[dictionary]

enumeration (char)
Permitted value(s) for the defined item.
May appear in list as essential element of loop structure.

[enumeration]

enumeration_default (char)
The default value for the defined item if it is not specified explicitly. If a data value is not declared, the default is assumed to be the 'most likely' or 'natural' value.

[enumeration_default]

enumeration_detail (char)
A description of the permitted value(s) for the defined item, as identified by enumeration.
May appear in list containing enumeration.

[enumeration]

enumeration_range (char)
The range of values permitted for a defined item. This can apply to 'numb' or 'char' items which have a preordained sequence (e.g. numbers or alphabetical characters). The minimum value 'min' and maximum value 'max' are separated by a colon character. If 'max' is omitted, then the item can have any permitted value greater than or equal to 'min'.

Examples: '-4:10', 'a:z', 'B:R', '0:'. [enumeration_range]

example (char)
An example value of the defined item.
May appear in list as essential element of loop structure.

[example]

example_detail (char)
A description of an example value for the defined item.
May appear in list containing example.

[example]

list (char)
Signals whether the defined item is declared in a looped list.

The data value must be one of the following:

yes can only be declared in a looped list
no cannot be declared in a looped list
both declaration in a looped list optional

Where no value is given, the assumed value is 'no'. [list]

list_level (numb)
Specifies the level of the loop structure in which a defined item with the attribute list 'yes' or 'both' must be declared.

The permitted range is $1 \rightarrow \infty$. Where no value is given, the assumed value is '1'. [list]

list_link_child (char)
Identifies data item(s) by name which must have a value which matches that of the defined item. These items are referred to as 'child' references because they depend on the existence of the defined item.

May appear in list. [list_link_child]

list_link_parent (char)
Identifies a data item by name which must have a value which matches that of the defined item, and which must be present in the same data block as the defined item. This provides for a reference to the 'parent' data item.

May appear in list. [list_link_parent]

list_mandatory (char)
Signals whether the defined item must be present in the loop structure containing other items of the designated category. This property is transferrable to another data item which is identified by related_item and has related_function set as 'alternate'.

The data value must be one of the following:

yes required item in this category of looped list
no optional item in this category of looped list

Where no value is given, the assumed value is 'no'. [list]

list_reference (char)
Identifies the data item, or items, which must be present (collectively) in a looped list with the defined data item for the loop structure to be valid. The data item(s) identified by list_reference provide a unique access code to each loop packet. Note that this property may be transferred to another item with related_function 'alternate'.

May appear in list. [list_reference]

`_list_uniqueness` (char)

Identifies data items which, collectively, must have unique values for the loop structure of the designated `_category` items to be valid. This attribute is specified in the definition of a data item with `_list_mandatory` set to 'yes'.

May appear in list. [list_uniqueness]

`_name` (char)

The data name(s) of the defined item(s). If data items are closely related or represent an irreducible set, their names may be declared as a looped sequence in the same definition.

May appear in list.

Examples: `'_atom_site_label', '_atom_attach_all _atom_attach_ring', '_index_h _index_k _index_l', '_matrix_l1 _matrix_l2 _matrix_l21 _matrix_l22'`. [name]

`_related_function` (char)

Specifies the relationship between the defined item and the item specified by `_related_item`. The following classifications are recognized. 'alternate' signals that the item referred to in `_related_item` has attributes that permit it to be used as an alternative to the defined item for validation purposes. 'convention' signals that the item referred to in `_related_item` is equivalent to the defined item except for a predefined convention which requires a different `_enumeration` set. 'conversion' signals that the item referred to in `_related_item` is equivalent to the defined item except that different scaling or conversion factors are applied. 'replace' signals that the item referred to in `_related_item` may be used identically to replace the defined item.

Appears in list containing `_related_item`.

The data value must be one of the following:

alternate	used alternatively for validation tests
convention	equivalent except for defined convention
conversion	equivalent except for conversion factor
replace	new definition replaces the current one

[related]

`_related_item` (char)

Identifies data item(s) which have a classified relationship to the defined data item. The nature of this relationship is specified by `_related_function`.

May appear in list as essential element of loop structure. [related]

`_type` (char)

The type specification of the defined item. Type 'numb' identifies items which must have values that are identifiable numbers. The acceptable syntax for these numbers is application-dependent, but the formats illustrated by the following identical numbers are considered to be interchangeable: 42, 42.000, 0.42E2, .42E+2, 4.2E1, 420000D-4, 0.0000042D+07. Type 'char' identifies items which need not be interpretable numbers. The specification of these items must comply with the STAR syntax specification of either a 'contiguous single-line string' bounded by blanks or blank-quotes, or a 'text string' bounded by semicolons as the first character of a line. Type 'null' identifies items which appear in the dictionary for data-definition and descriptive purposes. These items serve no function outside the dictionary files.

The data value must be one of the following:

numb	numerically interpretable string
char	character or text string
null	for dictionary purposes only

[type]

`_type_conditions` (char)

Codes defining conditions on the `_type` specification. 'su' permits a number string to contain an appended standard uncertainty number enclosed within parentheses, e.g. 4.37(5). 'esd' is a deprecated synonym for 'su', arising from the former use of the term 'estimated standard deviation' for 'standard uncertainty', and permitting a number string to contain an appended standard uncertainty within parentheses, e.g. 4.37(5). 'seq' permits data to be declared as a sequence of values separated by a comma <,> or a colon <:>. The sequence $v_1, v_2, v_3 \dots$ signals that v_1, v_2, v_3 etc. are alternative values. The sequence $v_1:v_2$ signals that v_1 and v_2 are the boundary values of a continuous range of values satisfying the requirements of `_enumeration` for the defined item. Combinations of alternative and range sequences are permitted.

May appear in list.

The data value must be one of the following:

none	no extra conditions apply to the defined <code>_type</code>
esd	synonym for 'su'
seq	data may be declared as a permitted sequence
su	numbers <i>may</i> have s.u.'s appended within parentheses

Where no value is given, the assumed value is 'none'. [type_conditions]

`_type_construct` (char)

String of characters specifying the construction of the data value for the defined data item. The construction is composed of two entities: (1) data names; (2) construction characters. The rules of construction conform to the regular expression (REGEX) specifications detailed in IEEE (1991) and *International Tables for Crystallography* (2005), Volume G, Chapter 2.5.

References: IEEE (1991). *IEEE Standard for Information Technology – Portable Operating System Interface (POSIX) – Part 2: Shell and Utilities*, Vol. 1, IEEE Standard 1003.2-1992. New York: The Institute of Electrical Engineers. *International Tables for Crystallographic Data*, edited by S. R. Hall and B. McMahon. Heidelberg: Springer.

Where no value is given, the assumed value is '.*'.

Example: `'(_year) - (_month) - (_day)'` (a typical construction for `_date`).

[type_construct]

`_units` (char)

A unique code which identifies the units of the defined data item. A description of the units is provided in `_units_detail`.

Examples: 'K' (kelvins), 'C' (degrees Celsius), 'rad' (radians), 'e' (electrons), 'V' (volts), 'Dal' (daltons), 'm' (metres), 'kg' (kilograms), 's' (seconds). [units]

`_units_detail` (char)

A description of the numerical units applicable to the defined item and identified by the code `_units`.

[units]